



## Mantis

### Stereo Viewing Systems

for a wide range of inspection and material rework tasks

- Patented optical technology for fatigue-free viewing and superb image quality
- Wide range of magnification options (to x20)
- Long working distances; large depths of field
- Shadow-free true colour LED illumination

# Mantis...

## Compact, Elite, Macro?

The Mantis family is a unique range of patented optical systems without eyepieces, for intricate tasks requiring superb quality viewing over long periods of time.

Mantis is in use in tens of thousands of sites worldwide and has become the accepted standard for ergonomics and high performance magnification.

The latest generation of Mantis incorporates the most modern advances in optical design, moulded plastics and LED illumination.

Vision Engineering has designed and manufactured world leading optical systems since 1958. The company's patented optical viewers, microscopes and measuring systems are manufactured in Vision Engineering factories in the UK and the USA.

The stereo eyepieceless Mantis viewers have a wide range of applications; it is used throughout manufacturing industries (electronics, precision engineering, plastics, medical devices) and life science laboratories around the world.

Advantages of the next generation Mantis are:

- Entry level, low investment versions
- Compact, functional units
- Wide range of magnification options (to x20)
- Shadow-free LED cold illumination, both surface and substage
- Long working distances; large depths of field
- Stable structures for high magnification viewing



### Mantis Compact

Mantis Compact excels in the low magnification range for inspection or manipulation tasks where bench magnifiers have traditionally been used. Mantis Compact has a small footprint and low investment cost giving a superb price / performance ratio.



### Mantis Elite

Mantis Elite offers a wider, higher performance specification including high magnification, large field of view, long working distance and head tilt capability. Mantis Elite has enhanced optical performance, making it a perfect alternative to traditional stereo microscopes for a wide range of inspection, preparation and manipulation tasks requiring hand-to-eye co-ordination.



### Mantis Macro

Mantis Macro offers a straight through in-line view of the subject, similar in operation to a bench magnifier, but with increased optical clarity and magnification. Mantis Macro offers a comparatively high magnification for an in-line viewer making it ideal for tasks which require exceptional hand-eye co-ordination and increased magnification.

**Mantis Compact** is a high value, low investment stereo viewer excelling in the low magnification range for inspection or manipulation tasks where bench magnifiers have traditionally been used.

Patented optical technology allows operators freedom of head movement for superb ergonomics and hand-eye co-ordination, with the ability to wear glasses if required. Operators can increase productivity and improve quality, at an affordable price.

- High value, low investment system
- Superior ergonomics for improved productivity and increased throughput
- Long working distances for easy sample manipulation and rework
- x2, x4 and x6 quick change objectives
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing
- Superb hand-eye co-ordination for inspection and manipulation tasks
- Patented eyepieceless optics maximise head freedom providing superb ergonomics and reduced eye fatigue



Mantis Compact, with counter-balanced universal stand, for flexibility and ease of use.



High stability bench stand, with integral focus and dimmable substage illumination.



Articulated arm, designed specifically for applications requiring extended reach, without compromising stability.

## Options



### Floating Stage

Provides smooth and sensitive control allowing for samples to be accurately inspected. For use with bench stand only.



### UV Lighting

For UV inspection applications and fast and accurate fault detection.



### Secondary Link Arm

A secondary link increases total reach of articulated arm to 847.5mm and provides added flexibility and manoeuvrability.



### Floor Stand

Ideal for inspection where subjects are immobile or require a standing position. For use in conjunction with articulated arm. Lift, swing, tilt and rotate capability.

### Optical Data

Objective Lenses	Working Distance	Field of View
x2	167mm	45.0mm
x4	96mm	27.5mm
x6	73mm	19.2mm

### Accessories

Lens protection caps  
Dust cover  
Replacement LED array



Buy Mantis Compact online - visit [www.visioneng.com/shop](http://www.visioneng.com/shop)



**Mantis Elite** is a high performance stereo microscope, offering superb optical performance with magnification options up to x20, making it a perfect alternative to more traditional stereo microscopes.

Large fields of view and generous working distances allow for a wide range of inspection, preparation and manipulation tasks to be carried out, all with exceptional hand-eye co-ordination.



Mantis Elite, with counter-balanced universal stand for flexibility and ease of use.

- High value, high specification patented design with superb optical performance
- x2 - x20 magnification options with quick change turret allows users to switch between low magnification inspection and high magnification fine detail tasks
- Patented eyepieceless optics maximise head freedom providing superb ergonomics and minimal eye fatigue
- Superior ergonomics for improved productivity and increased throughput
- Superb hand-eye co-ordination for inspection and manipulation tasks
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing
- Long working distance and large field of view for easy sample manipulation and rework



High stability bench stand with integral focus, dimmable substage illumination and floating stage (optional).



Articulated arm, designed specifically for applications requiring extended reach, without compromising stability.

## Options



### Floating Stage

Provides smooth and sensitive control allowing for samples to be accurately inspected. For use with bench stand only.



### Episcopic Illuminator

Through-the-lens illumination for the inspection of bore holes and complex internal/external features. Iris control for precise light positioning.



### UV Lighting

Switchable UV-white light illumination for UV inspection applications and fast and accurate fault detection.



### Secondary Link Arm

A secondary link increases total reach of articulated arm to 847.5mm and provides added flexibility and manoeuvrability.



### Floor Stand

Ideal for inspection where subjects are immobile or require a standing position. For use in conjunction with articulated arm. Lift, swing, tilt and rotate capability.

## Optical Data

Objective Lenses	Working Distance	Field of View
x2	160mm	57.0mm
x4	96mm	34.0mm
x6	68mm	23.0mm
x6 SLWD*	112mm	20.0mm
x8	59mm	17.0mm
x10	54mm	13.5mm
x15	40mm	8.8mm
x20	29mm	6.5mm

## Accessories

Lens protection caps  
Dust cover  
Replacement LED array

\* cannot be used together with x2 or x20 lens

Unlike other Mantis, which have an upright optical path, the **Mantis Macro** provides straight through in-line viewing which makes the co-ordination of hand and eye even easier.

Mantis Macro offers a straight through in-line view of the subject, similar in operation to a bench magnifier but with increased magnification and optical clarity making it ideal for tasks which require exceptional hand-eye co-ordination and increased magnification.




Mantis Macro, with counter-balanced universal stand and 30° tilting head facility, for flexibility and ease of use. Straight through in-line view for optimal hand-eye co-ordination and maximum working distance.

- Patented eyepieceless optical technology expands the exit pupil providing head freedom and eye relief for excellent ergonomics
- Straight through in-line optical path offers superb hand-eye co-ordination for inspection and manipulation tasks
- x2.5 –x5.0 magnification with quick change turret allows user to switch between magnifications
- Superior ergonomics for improved productivity and increased throughput
- Long working distance and large field of view for easy sample manipulation and rework
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing

Optical Data		
Objective Lenses	Working Distance	Field of View
x2.5	116mm	48.6mm
x5.0	66mm	23.8mm

Accessories
Lens protection caps
Dust cover
Replacement LED array

## Universal Stand




### Mantis Compact

**Dimensions:**  
 A = 565mm - 775mm  
 B = 335mm - 545mm  
 C = 395mm - 605mm  
 D = 110mm - 320mm  
**Unpacked weight:**  
 Head 2.1kg Stand 3.3kg  
**Packed weight:**  
 Head 4.1kg Stand 4.6kg

### Mantis Elite


**Dimensions:**  
 A = 593mm - 802mm  
 B = 352mm - 622mm  
 C = 415mm - 624mm  
 D = 103mm - 312mm  
**Unpacked weight:**  
 Head 3.0kg Stand 3.3kg  
**Packed weight:**  
 Head 5.0kg Stand 4.6kg

### Mantis Macro



**Dimensions:**  
 A = 500mm - 700mm  
 B = 260mm - 450mm  
 C = 350mm - 570mm  
 D = 75mm - 300mm  
 E = 20° - 50°  
**Unpacked weight:**  
 Head 2.6kg Stand 3.3kg  
**Packed weight:**  
 Head 4.9kg Stand 4.6kg

## Bench Stand




### Mantis Compact

**Dimensions:**  
 A = 526mm - 641mm  
 B = 198mm  
 C = 487mm  
 D = 305mm  
 E = 123mm - 238mm  
**Unpacked weight:**  
 Head 2.1kg Stand 4.5kg  
**Packed weight:**  
 Head 4.1kg Stand 7.9kg

### Mantis Elite

**Dimensions:**  
 A = 538mm - 653mm  
 B = 198mm  
 C = 487mm  
 D = 305mm  
 E = 122mm - 237mm  
**Unpacked weight:**  
 Head 3.0kg Stand 4.5kg  
**Packed weight:**  
 Head 5.0kg Stand 7.9kg

## Articulated Arm



### Mantis Compact

**Dimensions:**  
 A = 880mm  
 B = 430mm  
 C = 510mm  
 D = 650mm  
 E = 290mm  
**Unpacked weight:**  
 Head 2.1kg Stand 11kg  
**Packed weight:**  
 Head 4.1kg Stand 13.5kg

### Mantis Elite

**Dimensions:**  
 A = 880mm  
 B = 430mm  
 C = 510mm  
 D = 650mm  
 E = 290mm  
**Unpacked weight:**  
 Head 3.0kg Stand 11kg  
**Packed weight:**  
 Head 5.0kg Stand 13.5kg

## Illumination

**Note:** All Mantis use a 9V DC external plug transformer, available in all worldwide plug configurations.

### Mantis Compact

Lighting Data		
Light intensity measured at subject plane with colour correction filters.		
20 LEDs	9,400 LUX	10,000 hours
Substage illumination (bench stand only)		
13 LEDs	1,200 - 4,000 LUX	10,000 hours

### Mantis Elite

Lighting Data		
Light intensity measured at subject plane with colour correction filters.		
24 LEDs	11,000 LUX	10,000 hours
Substage illumination (bench stand only)		
13 LEDs	1,200 - 4,000 LUX	10,000 hours

### Mantis Macro

Lighting Data		
Light intensity measured at subject plane with colour correction filters.		
40 LEDs	9,500 LUX	10,000 hours



Vision Engineering manufactures a comprehensive range of ergonomic stand-alone mono and stereo microscopes as well as a complete line of non-contact measuring systems.

## For more information...

Vision Engineering has a network of offices and technical distributors around the world. For more information, please contact your Vision Engineering branch, local authorised distributor, or visit our website.

Vision Engineering Ltd.  
**(Manufacturing)**  
Send Road, Send, Woking,  
Surrey, GU23 7ER, England  
Tel: +44 (0) 1483 248300  
Fax: +44 (0) 1483 223297  
Email: [generalinfo@visioneng.com](mailto:generalinfo@visioneng.com)

Vision Engineering Inc.  
**(Manufacturing & Commercial)**  
570 Danbury Road, New Milford,  
CT 06776 USA  
Tel: +1 (860) 355 3776  
Fax: +1 (860) 355 0712  
Email: [info@visioneng.com](mailto:info@visioneng.com)

Vision Engineering Ltd.  
**(Central Europe)**  
Anton-Pendele-Str. 3,  
82275 Emmering, Germany  
Tel: +49 (0) 8141 40167-0  
Fax: +49 (0) 8141 40167-55  
Email: [info@visioneng.de](mailto:info@visioneng.de)

Vision Engineering Ltd.  
**(France)**  
1 Rue de Terre Neuve, ZA Courtaboeuf,  
91967 Les Ulis Cedex, France  
Tel: +33 (0) 164 46 90 82  
Fax: +33 (0) 164 46 31 54  
Email: [info@visioneng.fr](mailto:info@visioneng.fr)

Vision Engineering Ltd.  
**(Commercial)**  
Monument House, Monument Way West,  
Woking, Surrey, GU21 5EN, England  
Tel: +44 (0) 1483 248300  
Fax: +44 (0) 1483 248301  
Email: [generalinfo@visioneng.com](mailto:generalinfo@visioneng.com)

Vision Engineering Inc.  
**(Commercial West Coast USA)**  
745 West Taft Avenue, Orange,  
CA 92865 USA  
Tel: +1 (714) 974 6966  
Fax: +1 (714) 974 7266  
Email: [info@visioneng.com](mailto:info@visioneng.com)

Nippon Vision Engineering  
**(Japan)**  
272-2 Saedo-cho, Tsuduki-ku,  
Yokohama-shi, 224-0054, Japan  
Tel: +81 (0) 45 935 1117  
Fax: +81 (0) 45 935 1177  
Email: [info@visioneng.jp](mailto:info@visioneng.jp)

Vision Engineering Ltd.  
**(Italy)**  
Via Cesare Cantù, 9  
20092 Cinisello Balsamo MI, Italy  
Tel: +39 02 6129 3518  
Fax: +39 02 6129 3526  
Email: [info@visioneng.it](mailto:info@visioneng.it)

Vision Engineering Ltd  
**(China)**  
11J, International Ocean Building,  
720 Pudong Avenue, Shanghai,  
200120, P.R. China  
Tel: +86 (0) 21 5036 7556  
Fax: +86 (0) 21 5036 7559  
Email: [info@visioneng.com.cn](mailto:info@visioneng.com.cn)

Vision Engineering  
**(India)**  
Tel: +91 (022) 2613 0699  
Fax: +91 (022) 2610 3845  
Email: [info@visioneng.co.in](mailto:info@visioneng.co.in)

Distributor

CE

Visit our multi-lingual website:  
[www.visioneng.com](http://www.visioneng.com)

Disclaimer – Vision Engineering Ltd. has a policy of continuous development and reserves the right to change or update, without notice, the design, materials or specification of any products, the information contained within this brochure/datasheet and to discontinue production or distribution of any of the products described.