

SUBITO Precision Bore Measuring Instrument

for measuring of
blind bore diameters

SS/SSV



SERIES 140-146

Delivery: Holder, measuring slides and contact pin tungsten carbide as standard, in wooden box, w/o dial gauge.

Version with $h = 1$ mm: for measuring very close to the bottom of the bore.

SUBITO SS

Application range [mm]	front distance „h“ [mm]	meas. slides carbide Art.-No.	meas. slides ruby Art.-No.	holder SS Art.-No.
20 - 50	1,5	140 00000	140 00001	140 00024
20 - 60	1,5	141 00000	141 00001	141 00024
50 - 110	1,5	142 00000	142 00001	142 00027
50 - 140	1,5	143 00000	143 00001	143 00027
110 - 300	2,0	144 00000	144 00001	144 00032
110 - 400	2,0	145 00000	145 00001	145 00032
- 600	2,0	<i>on inquiry</i>		

20 - 50	1,0	140 00002		
20 - 60	1,0	141 00002		
50 - 110	1,0	142 00002		
50 - 140	1,0	143 00002		
110 - 300	1,0	144 00002		
110 - 400	1,0	145 00002		

Delivery: 1 short upper part, 2 blind bores measuring heads, measuring slides, in wooden box, w/o dial gauge.

SUBITO BLIND BORES VARIO SSV

Combination of two instruments:
20 - 50 and 50 - 140 mm

20 - 140	1,0	146 00002	
20 - 140	1,5	146 00000	146 00001




SUBITO SS
for blind bores

s: travel

D: diameter to be measured

h: front distance



front distance h for SUBITO SS