

# STC2-G STC2-G-BT

Digital Torque Screwdriver

Assembly

Inspection

Digital

Bit

Direct Reading

Rechargeable

RoHS



- Ideal for tightening and inspection operation
- 1000 data memory storage and data output function
- LED (White, Blue, and Yellow/Red) indicator

Direction



STC200CN2-G

Model		Torque Range								Overall Length [mm]	Weight [g]
		[cN·m]		[kgf·cm]		[lbf·in]		[ozf·in]			
standard version	Bluetooth version	Min.-Max.	1 digit	Min.-Max.	1 digit	Min.-Max.	1 digit	Min.-Max.	1 digit		
STC50CN2-G	<b>NEW</b> STC50CN2-G-BT	10-50	0.05	1-5	0.005	1-4.4	0.005	15-70	0.05		
STC200CN2-G	<b>NEW</b> STC200CN2-G-BT	40-200	0.2	4-20	0.02	4-17	0.02	-	-	230	325
STC400CN2-G	<b>NEW</b> STC400CN2-G-BT	80-400	0.5	8-40	0.05	8-35	0.05	-	-		


Accuracy ±1%

**Note**

1. Bits are sold separately. Refer to page 11.
2. Bits size as below
3. Refer to page 30 for condition of wireless equipment in each country.
4. Data output of standard version is through USB only.
5. Data output of Bluetooth version is through USB and Bluetooth.

**Standard Accessories**

USB cable/384, AC adapter/BA-7, and Battery pack/BP-7. Refer to page 47.



White LED light (80% of target torque)



Blue LED light (Achieving target torque)



Yellow & Red flashing LED light (Over torque)

Display can be turned upside down with keypad operation.

[EX.] Torque checking figure for torque screwdriver



STC2-G

## STC2-G Optional Accessories



AC Adapter (P.47)

Model	Applicable Model
BA-7	STC2-G



Battery Pack (P.47)

Model	Applicable Model
BP-7	STC2-G



PC Connecting Cable (P.47)

Model	Applicable Model
384	STC2-G (P.10), ST3-G (P.56), ATGE-G (P.58), BTGE-G (P.59)